ARDEX E 25™

Resilient Emulsion

Specially designed additive for select ARDEX underlayments and toppings

Improves modulus of elasticity and the cohesive and flexural strengths for challenging applications and high-stress areas

Mix with select ARDEX self-leveling surface products for areas subject to heavy traffic, heavy rolling or static load and/or other high-stress conditions

Mix with select ARDEX patching underlayments for installation over above-grade VCT or as an embossing filler for residential sheet vinyl

Mix with ARDEX K 15 for certain, specialized applications; contact the ARDEX Technical Service Department for guidance

For dry, interior areas only

For substrate preparation, mixing and application instructions, please see the technical data sheet for the ARDEX underlayment or topping being installed.

ARDEX Americas
400 Ardex Park Drive
Aliquippa, PA 15001 USA
888-512-7339
www.ardexamericas.com

ARDEX E 25™

Resilient Emulsion

Notes

Intended for use by professional contractors who are trained in the application of this product and/or similar products. Not sold by ARDEX through home improvement centers. Never mix with cement or additives outside of our written recommendations. For information on ARDEX Academy trainings, visit ardexamericas.com.

In accordance with industry standards, and to determine the suitability of the products for the intended use, always install an adequate number of properly located test areas, to include the finish flooring or sealers. Test installations are always required over adhesive residues. As floor coverings and sealers vary, always contact and rely upon the floor covering or sealer manufacturer for specific directives such as maximum allowable moisture content, adhesive selection and intended end use of the product.

When not in use, keep the container tightly sealed. Open and reseal as necessary. Store container at room temperature (50° to 90°F / 10° to 32°C). If the container is exposed to temperatures below 50°F (10°C) and appears congealed or stringy, do not use and contact the ARDEX Technical Service Department for more information.

Observe the basic rules of concrete work. If the installation is not proceeding as expected: Contact the ARDEX Technical Service Department before proceeding further. Dispose of packaging and residue in accordance with prevailing regulations. Do not flush material down drains. Do not reuse packaging.

Precautions

Carefully read and follow all precautions and warnings on the product label. For complete safety information, please refer to the Safety Data Sheet (SDS) available at: www.ardexamericas.com.

Technical Data According to Manufacturer Quality Standards

Packaging:	1 gal. (3.8 L) container
Storage:	Store in a cool, dry area. Do not expose container to sun. Keep from freezing. Keep from heat. Keep container tightly closed when not in use.
Shelf Life:	One year
Warranty:	ARDEX L.P. Standard Limited Warranty applies. For full warranty details: ardexamericas.com/services/warranties.

Made in the USA. © 2026 ARDEX, L.P. All rights reserved. Content updated 2026-09-29. Supersedes all previous versions. Latest version available at ardexamericas.com.

Visit www.youtube.com/ARDEX101 to watch ARDEX product demonstration videos. For recommended installation tools, visit DTA USA at www.dtausagroup.com. For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App.

Available on the iPhone App Store | ANDROID APP ON Google play | YouTube

ARDEX Americas
400 Ardex Park Drive
Aliquippa, PA 15001 USA
888-512-7339
www.ardexamericas.com