SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

Product Identifier : ARDEX EP 2000[™] Resin (Part A)

Product ID Number : 50011570

Trade Name/Synonyms : ARDEX EP 2000 Resin

Material Use : Epoxy resin of two-part system for substrate preparation

Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.

Manufacturer's name and address:

ARIEN

400 Ardex Park Dr.

Aliquippa, PA 15001 USA

Information Telephone No. : 1-888-512-7339 or 1-724-203-5000 Website Address : http://www.ardexamericas.com

24 Hr Emergency Telephone # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Skin Sensitizer Category 1 Eye Irritant Category 2A Skin Irritant Category 2

GHS Pictograms



Signal Word Warning

Hazard Statements Causes serious eye irritation.

May cause an allergic skin reaction.

Causes skin irritation.

Precautionary Statements Do not get in eyes, on skin, or on clothing. Avoid breathing vapors or dust. Use

only outdoors or in a well-ventilated area. Wash hands and exposed skin thoroughly after handling. Wear protective gloves and eye protection.

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents / container in accordance with

federal, state, and local laws. Do not allow product to enter drains.

Hazards Not Otherwise Identified : None

Unknown Acute Toxicity Content : < 5% of this product consists of ingredients with unknown acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	% (by weight)	
Bisphenol A / epichlorohydrin resin	25068-38-6	60.00 - 100.00	
Phenol-formaldehyde polymer	28064-14-4	10.00 - 30.00	
2-Ethylhexyl glycidyl ether	2461-15-6	10.00 - 30.00	

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

SECTION 4 – FIRST AID MEASURES

General : Get medical attention if you feel unwell.

Inhalation : Remove person to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention.

Skin contact : Remove contaminated clothing. Flush affected skin with soap and water. If irritation

persists: seek medical attention/advice.

Eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical advice/attention.

Ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel

unwell.

Notes for Physician : Treat symptomatically.

Signs and symptoms of short-term (acute) exposure

Inhalation : Inhalation of vapors may cause mild irritation of the respiratory system. Symptoms

may include coughing.

Skin : Causes irritation. Symptoms may include redness and itching.

Eyes : Causes irritation. Symptoms may include redness, itching, tearing, or pain.

Ingestion : May cause stomach pain with nausea and vomiting.

Effects of long-term (chronic) exposure

 Prolonged inhalation may cause adverse lung effects with symptoms including coughing and shortness of breath. Some individuals may experience a sensitization reaction of the skin after an initial exposure. Subsequent exposures

may cause a hypersensitive skin reaction (rash, swelling).

Indication of need for immediate medical attention or special treatment

: Difficulty breathing persists after removing the person to fresh air.

Any exposure to the eye which causes irritation.

Ingestion.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable extinguishing media

: Carbon dioxide, dry chemical powder, alcohol resisant foam, water mist/fog.

Unsuitable extinguishing media

: Water jet may spread the flames.

Hazardous combustion products

: Carbon oxides and/or low molecular weight hydrocarbons.

Special fire-fighting procedures/equipment

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

: Not flammable. Other Flammability properties are found in Section 9.

NFPA Rating : 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 2 Flammability 1 Reactivity 0 Special Hazards 0

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear chemically resistant personal protective equipment during cleanup. Restrict

access to area until completion of clean-up. All persons dealing with clean-up

should wear the appropriate chemically protective equipment.

Protective equipment : Refer to Section 8 for additional information on acceptable personal protective

equipment.

Emergency procedures : This product does not contain any chemicals which require reporting spills or

releases to the U.S. EPA. In case of a spill or release, call the emergency number

listed in Section 1 for advice.

US CERCLA Reportable quantity (RQ): None reported.

Spill response / clean-up : Ventilate area of release. Stop spill or leak at source if safely possible. Contain

product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later

disposal Notify the appropriate authorities as required.

Environmental precautions : Do not allow product to enter waterways. Do not allow material to contaminate

ground water system.

Disposal of spilled material : See Section 13.

SECTION 7 – HANDLING AND STORAGE

Safe handling procedures : Observe good hygiene standards. Do not eat, drink or smoke in the work area.

Wash thoroughly after handling. Avoid contact with skin and eyes. Avoid repeated or prolonged skin contact. Avoid breathing vapors. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed. Use only

with adequate ventilation.

Storage requirements : Store in a cool, dry, well-ventilated area. Store away from heat and open flame.

Avoid storing in direct sunlight. Store in original container. Keep tightly closed when

not in use. Do not reuse empty container without commercial cleaning or

reconditioning.

Incompatible materials : Strong oxidizing agents.

Special packaging materials: Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure limits : No exposure limits have been established for the product. Below are exposure limits for the ingredients in the product.

Ingredients	CAS#	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Bisphenol A / epichlorohydrin resin	25068-38-6	N/Av	N/Av	N/Av	N/Av
Phenol-formaldehyde polymer	28064-14-4	N/Av	N/Av	N/Av	N/Av
2-Ethylhexyl glycidyl ether	2461-15-6	N/Av	N/Av	N/Av	N/Av

Engineering measures : Use general or local exhaust ventilation to maintain air concentrations below

recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.

Eye / face protection : Chemical goggles or safety glasses must be worn when using this product. A face

shield is recommended if splashing is possible.

Skin protection : Wear chemical resistant protective clothing and impervious gloves. Materials such

as nitrile rubber or Viton (fluorocarbon rubber) are recommended.

Body protection: Where extensive exposure to product is possible, use resistant coveralls, apron and

boots to prevent contact.

Respiratory protection : If work process generates excessive quantities of vapor or dust, or exposures

exceeding any PEL, wear an appropriate NIOSH approved organic vapor

respirator.

Site safety equipment : An eyewash station and safety shower should be made available in the immediate

working area.

General hygiene precautions : Avoid contact with eyes, skin and clothing. Do not breathe vapors. Do not eat,

drink or smoke when using this product. Clean all equipment and clothing at end of

each work shift.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid Appearance : Colorless liquid

Odor Characteristic Odor threshold : N/Av рΗ Specific gravity : 1.1 – 1.2 : N/Av **Boiling point** : N/Av Coefficient of water/oil distribution : N/Av Melting/Freezing point : N/Av Solubility in water : Insoluble Vapor pressure (mm Hg @ 20°C / 68°F) : N/Av Evaporation rate (n-Butyl acetate = 1) : N/Av Vapor density (Air = 1) : N/Av Volatiles (% by weight) : N/Av

Volatile organic compounds (VOCs) : 12.4 g/L, A+B, per ASTM D2369

Decomposition temperature: N/AvFlammable Classification: Not FlammableFlash point: >212°F (>100°C)Lower flammable limit (% by vol): Not availableFlash point method: Setaflash closedUpper flammable limit (% by vol): Not available

Auto-ignition temperature : > 840°F (450°C) Oxidizing properties : None

Flame projection length : Not available Flashback observed : Not available

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Viscosity : Not available

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

Reactivity : Product reacts with amines to form polymers. Heat is evolved by this reaction. **Stability and reactivity** : Stable under the recommended storage and handling conditions prescribed.

Hazardous polymerization : Hazardous polymerization does not occur.

Conditions to avoid : Avoid prolonged exposure to heat.

Materials to avoid and incompatibility

: Oxidizing agents.

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of Exposure : Inhalation: YES Skin Absorption: NO Skin and Eyes: YES Ingestion: YES

Signs and symptoms of exposure

: See Section 4.

Calculated Acute Toxicity Estimates for the Product

Inhalation : N/Av

 $\begin{array}{lll} \textit{Oral} & : & > 2,000 \text{ mg/kg} \\ \textit{Dermal} & : & > 2,000 \text{ mg/kg} \\ \end{array}$

Toxicological data : See below for individual ingredient acute toxicity data.

	LC50 (4 hr)	LD50		
Ingredients	Inhalation, rat	Oral, rat	Dermal, rabbit	
Bisphenol A / epichlorohydrin resin	N/Av	11,400mg/kg	> 23,500 mg/kg	
Phenol-formaldehyde polymer	N/Av	> 5000 mg/kg	> 2000 mg/kg	
2-Ethylhexyl glycidyl ether	N/Av	7800 mg/kg	> 2000 mg/kg	

Skin corrosion/irritation: Causes skin irritation.Serious eye damage/eye irritation: Causes serious eye irritation.

Respiratory or skin sensitization : Contains components which are known to cause skin sensitization reactions. Does

not contain known respiratory sensitizers.

Germ cell mutagenicity : None known.

Carcinogenic status : No components present in concentration greater than 0.1% are listed as

carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive toxicity : None known.

Specific Target Organ Toxicity, Single Exposure

: None known.

Specific Target Organ Toxicity, Repeated Exposure

: None known.

Aspiration hazard : None known.

Other important hazards : See Section 2 for additional information.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : The product should not be allowed to enter drains or water courses, or be

deposited where it can affect ground or surface waters.

Ecotoxicological : No data is available on the product itself.

Persistence and degradability : No data available.

Bioaccumulative potential : No data available.

Mobility in the soil : No data available.

PBT and vPvB assessment : No data available.

Other adverse effects : No data available.

SECTION 13 – DISPOSAL CONSIDERATION

Handling for disposal : Handle waste according to recommendations in Section 7.

Methods of disposal : Dispose in accordance with all applicable federal, state, provincial and local

regulations. Contact your local, state, provincial or federal environmental agency

for specific rules.

Packaging : Handle contaminated packaging in the same manner as the product.

RCRA : For disposal of unused or waste material, check with local, state and federal

environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN 3082	Environmentally hazardous substances, liquid, n.o.s. (Contains: Bisphenol A / epichlorohydrin resin)	9	III	•
TDG Additional Information	None				
49 CFR/DOT	UN 3082	Environmentally hazardous substances, liquid, n.o.s. (Contains: Bisphenol A / epichlorohydrin resin)	9	III	9
49 CFR/DOT Additional Information	None				

Marine Pollutant : Yes

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Skin Sensitizer Category 1 Eye Irritant Category 2A Skin Irritant Category 2

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right to Know Laws

California Proposition 65: See product label for information regarding Proposition 65.

Other State Right to Know Laws: No chemicals listed in other state RTK Laws.

SECTION 16 – OTHER INFORMATION

HMIS Rating : *- Chronic Hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: *2 Flammability 1 Physical Hazard 0 PPE: Gloves, safety glasses

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability

Act of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency GHS: Globally Harmonized System HPR: Hazardous Products Regulations

IARC: International Agency for Research on Cancer

Inh: Inhalation N/Av: Not Available N/Ap: Not Applicable

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user determines the adequacy of the safety procedures employed during the use of this product. No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By: ARDEX L.P. 400 Ardex Park Drive Aliquippa, PA, U.S.A. 15001

(724) 203-5000 Visit our Website: http://www.ardexamericas.com

Revision date: : 21-Jun-2021

End of Document