

ARDEX CG™ Concrete Guard™ 2.0

High-Performance, Waterborne
Acrylic Concrete Sealer

Key Features

- Seals and protects all uncoated cementitious surfaces, including ARDEX Toppings
- Durable and abrasion-resistant on interior and exterior absorbent concrete and masonry surfaces
- VOC compliant

Installation

- **Packaging:** 1 Gallon / 3.79 L Container
- **Coverage:**
 - Gray over broom finish: 150-200 sq. ft. (14-19 sq. m) per gallon
 - Gray over smooth finish: 200-400 sq. ft. (19-37 sq. m) per gallon
 - Clear over broom finish: 200-300 sq. ft. (19-28 sq. m) per gallon
 - Clear over smooth finish: 400-600 sq. ft. (37-56 sq. m) per gallon
- **Apply with:** 3/8" (9.5 mm) nap roller
- **Drying time:** (minimum at 70°F/21°C) to touch: 1 hour
- **Apply second coat:** 4 to 5 hours
- **Walkable:** 24 hours

Performance

- **Solids content:** 40%
- **VOC:** Clear – 95 g/L; Grey – 97 g/L (per SCAQMD Method 304)
- **Exceeds ADA requirements**
- **USDA/FDA FSIS Directive 1000.4, Revision 1 Approved**

For more information visit www.ardexamericas.com.



AMERICAS

ARDEX Americas
400 Ardex Park Drive
Aliquippa, PA 15001
888-512-7339

www.ardexamericas.com