


BUILT BY
YOUTM
backed by **ARDEX**



ARDEX AMERICAS | Engineered Concrete Repair Systems

	Structural Repair	Single Component	Polymer Modified	Corrosion Inhibitor	Micro silica	Horizontal	Vertical	Overhead	Form & Pour	Pumpable	Trowel-Grade	Walk on or seal	Minimum Thickness	Maximum Thickness
ARDEX TRM™	•	•			•	•			•	•		6 hours	1/2" to 4" neat (12 mm to 10.cm)	8" (20 cm) with aggregate
ARDEX ERM™	•	•	•	•		•					•	3-7 days	1/4" to 2" neat (6 mm to 5 cm)	8" (20 cm) with aggregate
ARDEX FP™	•	•				•	•	•	•	•		72 hours	1/2" to 4" neat (12 mm to 10 cm)	8" (20 cm) with aggregate
ARDEX CP™		•	•			•	•				•	Walk 2 Seal 4	1/4" to 1/2" neat (6 to 12 mm)	1" (2.5 cm) with aggregate
ARDEX CD™		•	•			•	•				•	2 hours	1/16" (1.5 mm)	1/8 to 1/2" (3 to 12 mm) in small defined areas
ARDEX CD FINE™		•	•			•	•				•	2 hours	1/32" (0.75 mm)	1/8 to 1/2" (3 to 12 mm) in small defined areas
ARDEX K 301™		•	•			•				•		3 hours	1/4" (6 mm) neat	3/4 to 2" neat (18 mm to 5 cm) with aggregate
ARDEX CG Concrete Guard™		•				•	•				•	24 hours	N/A	N/A
ARDEX ARDIFIX™						•						45 minutes	N/A	No Limits
ARDEX OVP™		•	•				•	•			•	2-3 hours	Featheredge	Any in well-defined areas
ARDEX TWP™		•	•				•				•	15-60 minutes	Featheredge	Any in well-defined areas
ARDEX B 20™	•	•	•	•		•	•	•			•	3-7 days	1/4" (6 mm)	2" (5 cm) 8" (20 cm) in 2" lifts
ARDEX BACA™				•	•	•	•	•	•			N/A	BONDING AGENT single 20 mil (500 micron) coat	ANTI-CORROSION AGENT two 10 mil (250 micron) coats
ARDEX EP 2000™						•						Walk 6 Install 16	N/A	N/A
ARDEX P 71™		•				•						wet	N/A	N/A

The chart information represents basic product recommendations. Always refer to the ARDEX Technical Data Sheets or website prior to installation for specific product installation guidelines. ARDEX Technical Department can be reached at 888-512-7339

AF - 173 01/22
www.ardexamericas.com