

BUILT BY  
**YOU**<sup>™</sup>  
backed by **ARDEX**



## ARDEX AMERICAS | Self-Leveling Underlayments

Product Selection Chart		Over concrete	Over ceramic tile and terrazzo	Over non-water-soluble adhesive residue	Well bonded VCT	Epoxy Coating Systems	Metal	Over wood	Over gypsum	Primer, Mechanical Prep	Pumpable	On/Above/Below Grade	Base cemento portland	Cement Hybrid	Can be tapered	Mix with water only	Two Component	Maximum thickness neat	With aggregate	Hours to walk on	Hours to install moisture insensitive tile & stone	Hours to install most flooring	Compressive strength (ASTM C109 Modified) at 28 days	Coverage	RH Limit
<a href="#">ARDEX K 15®</a>		●	●	●		●	●	●		Yes	●	OAB	●		●	●		1 1/2" 4 cm	5" 12 cm	2 to 3	6	16	5500 psi (386 kg/cm <sup>2</sup> )	30 ft <sup>2</sup> at 1/4" (2.79 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX K 40™ RAPID</a>		●	●	●		●				Yes	●	OAB	●		●	●		1" 2.5 cm		1 to 2	2	2	8000 psi (562 kg/cm <sup>2</sup> )	56 ft <sup>2</sup> at 1/8" (5.2 m <sup>2</sup> at 3 mm)	99% RH
<a href="#">ARDEX K 13™</a>	High Flow	●	●	●		●				Yes	●	OAB	●		●	●		1 1/2" 4 cm		2 to 3	6	16	5300 psi (371 kg/cm <sup>2</sup> )	28 ft <sup>2</sup> at 1/4" (2.6 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX V 1300™</a>		●	●	●		●		●		Yes	●	OAB	●		●	●		2" 5 cm	5"+ 12 cm+	2 to 3	6	24	5500 psi (386 kg/cm <sup>2</sup> )	29 ft <sup>2</sup> at 1/4" (2.7 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX V 1200™</a>		●	●	●		●				Yes	●	OAB	●		●	●		2" 5 cm		2 to 3	6	24	4500 psi (316 kg/cm <sup>2</sup> )	25 ft <sup>2</sup> at 1/4" (2.3 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX V 1000™</a>		●	●							Yes	●	OAB	●		●	●		1 1/4" 3 cm		4 to 5	6	24	4400 psi (309 kg/cm <sup>2</sup> )	25 ft <sup>2</sup> at 1/4" (2.3 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX K 10™</a>		●	●	●		●				Yes	●	OAB	●		●	●		1" 2.5 cm		2 to 3	6	24	4700 psi (329 kg/cm <sup>2</sup> )	50 ft <sup>2</sup> at 1/8" (4.5 m <sup>2</sup> at 3 mm)	99% RH
<a href="#">ARDEX K 60™ ARDITEX</a>		●	●	●		●	●	●		No		OAB	●		●		●	1/2" 12 mm		2 to 3	6	24	3500 psi (246 kg/cm <sup>2</sup> )	42 ft <sup>2</sup> at 1/8" (3.9 m <sup>2</sup> at 3 mm)	100% RH
<a href="#">ARDEX LU 100™</a>		●	●	●	●	●		●		Yes	●	A		●	●	●		2" 5 cm	5" 12 cm	3	72	72	5000 psi (350 kg/cm <sup>2</sup> )	22 ft <sup>2</sup> at 1/4" (2 m <sup>2</sup> at 6 mm)	99% RH
<a href="#">ARDEX K 22 FT™</a>		●	●	●	●	●		●		Yes	●	A		●	●	●		1 1/4" 3 cm	2" 5 cm	2 to 3	72	24*	6000 psi (420 kg/cm <sup>2</sup> )	50 ft <sup>2</sup> at 1/8" (4.5 m <sup>2</sup> at 3 mm)	99% RH
<a href="#">ARDEX K 34™</a>		●	●			●		●		Yes	●	OAB	●		●	●		3" 7.6 cm		2 to 3	24*	24*	3000 psi (211 kg/cm <sup>2</sup> )	34 ft <sup>2</sup> at 1/4" (3.15 m <sup>2</sup> at 6 mm)	99% RH

The chart information represents basic product recommendations. Always refer to the ARDEX Technical Data Sheets or website prior to installation for specific product installation guidelines. \*Mat test