

ARDEX E 25™

Resilient Emulsion

Improves the modulus of elasticity and the cohesive and flexural strengths of ARDEX K 15® Premium Self-Leveling Underlayment and ARDEX K 500™ Self-Leveling Concrete Topping. Use with ARDEX K 500 for high stress areas subject to forklift traffic.

Install over: cutback and other adhesive residues, metal and the mesh-reinforced wood subfloor system

Key Features

- Part of the ARDEX K 15 and ARDEX E 25 Underlayment Systems
- Interior use

Installation

- **Packaging:** 1 gal (3.8 L)
- **Mixing ratio:**
 - ARDEX K 15 - Add 2 quarts with 6 quarts of water, then add powder
 - ARDEX K 500 - Add 2 quarts with 5 quarts of water, then add powder
- **Working time:** Based on powder product performance
- **Walkable:** Based on powder product performance
- **Install:** Based on powder product performance

Performance

Based on powder product performance



Top Photo: ARDEX K 15® Premium Self-Leveling Underlayment - Improves the modulus of elasticity and the cohesive and flexural strengths

Bottom Photo: ARDEX K 500™ - high stress areas subject to forklift traffic.



SUBSTRATE
PREPARATION



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com

AF 117 11/14