

ARDEX FORTI FINISH™

High Strength Self-Drying Finish Underlayment

ARDEX FORTI FINISH™ is a cement-based underlayment developed specifically for challenging environments such as hospitals where heavy rolling loads and high point loads are common. ARDEX FORTI FINISH will not contribute to mold, mildew and staining of floor covering.

Install over: concrete and prepared adhesive residues on concrete

Key Features

- Polymer-modified
- Self-drying matrix
- Mixes with water only
- Trowelable
- Interior use

Installation

- **General priming recommendations:** No priming required
- **Packaging:** 10 lb. (4.5 kg)
- **Coverage:** 40 sq. ft. per bag at 1/16" (3.7 m² at 1.5 mm)
- **Thickness:** Install from a true featheredge to any depth
- **Pot life:** 15 to 20 minutes
- **Install floor coverings:** 15 minutes

Performance

- **ASTM C109 mod (air cure only) Compressive Strength:**
 - 2000 psi (140 kg/cm²) at one day
 - Over 5000 psi (350 kg/cm²) at 7 days
 - Over 7800 psi (546 kg/cm²) at 28 days
- **VOC:** 0



SUBSTRATE
PREPARATION



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com

AF257 11/14