

ARDEX PANDOMO® K2

Loft Design Micro-Topping Compound

Self-drying topping for fast-track resurfacing of indoor concrete to produce a high-end, creatively designed ARDEX PANDOMO® Loft wear surface.

Key Features

- Trowelable
- Portland cement-based
- Use over new or existing interior concrete
- Highly durable surface
- Color with ARDEX PANDOMO® CC Color Concentrates

Installation

- **General priming recommendations:**
 - ARDEX EP 2000™ Substrate Preparation Epoxy Primer
- **Packaging:** 55 lbs. (25 kg)
- **Coverage:** 100 to 120 ft² (9.3 to 11.1 m²) per bag in 2 coats
- **Thickness:**
 - Install from 1/16" up to 3/16" (1.5 to 4.5 mm)
- **Working Time:** 10 minutes
- **Walkable:** 3 hours after second coat
- **Begin Processing:** 6 to 12 hours
- **Seal with ARDEX PANDOMO® ES/PS Protective Wear Layer System**

Performance

- **ASTM C191 Initial Set:** Approx. 10 minutes
- **ASTM C191 Final Set:** Approx. 45 minutes
- **ASTM C109 mod (air cure only) Compressive Strength:** 4600 psi (323 kg/cm²) at 28 days
- **ASTM C348 Flexural Strength:** 1400 psi (98 kg/cm²) at 28 days



For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google play.



Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training, click on ARDEX Academy.

© 2014 ARDEX Engineered Cements, L.P. All rights reserved.

AF397 06/15

ARDEX®
PANDOMO



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com