

HENRY®

The Professional's Formula For Success™



HENRY® 130

Thin Spread Floor Tile Adhesive



Thin-spread, solvent-free asphalt emulsion/latex-based adhesive designed to install vinyl composition tile (VCT) in commercial installations.

Use For:

Vinyl composition tile (VCT) and asphalt tile only.

Key Features & Benefits:

- 18-hour working time - Ideal for large commercial installations
- Can be used over "cutback" adhesive
- Moisture and alkali resistant - Allows installation on all grade levels of concrete

Bonds To:

Porous: Concrete, cementitious underlayments, APA grade underlayment plywood (untreated) and radiant heated subfloors where temperatures do not exceed 85°F (29.4°C) on all grade levels. Can also be used over properly primed gypsum underlayments (above-grade only).

Non-porous: Properly prepared "cutback" adhesive, existing well-bonded resilient flooring (not perimeter-bonded or cushion-backed), ceramic tile, terrazzo, marble, certain epoxy coatings, steel, stainless steel, aluminum, lead, copper, brass and bronze. Steel, stainless steel, aluminum, lead, copper, brass and bronze substrates must be mechanically abraded.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

Coverage:

For All Applications

U-Notch

1/32"D x 1/16"W x 5/64"A
350-400 sq. ft. / gal.



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com