

# HENRY®

The Professional's Formula For Success™



## HENRY® 256

### Dual Purpose Carpet and Sheet Flooring Adhesive



Installer-grade, dual-purpose adhesive that is excellent for light to moderate traffic areas.

#### Use For:

Carpet backed with jute\*, Action Bac®\* (polypropylene), urethane foam\*, latex foam (rubber)\*, unitary\*, unitary Action Bac®, hot melt, woven, urethane laminate and non-backed needle-punched\*. Also felt-backed sheet flooring. \*Extended 5-year warranty for these applications.

#### Key Features and Benefits:

- Aggressive early grab - helps reduce edge curl
- Short open time - for quicker installations
- Ample working time - accommodates a range of installations

#### Bonds To:

On all grade levels - concrete, well-bonded cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), terrazzo, ceramic tile, marble, certain epoxy coatings and existing, fully adhered, non-cushion backed resilient. Above grade only - well-bonded, properly primed gypsum

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING ([WWW.WWHENRY.COM](http://WWW.WWHENRY.COM))



#### Coverage:

**Rough-Backed Carpet: V-Notch**  
1/8"D x 1/8"W x 1/16"A  
90 - 108 sq. ft. / gal.

**Smooth-Backed Carpet: V-Notch**  
3/32"D x 3/32"W x 3/32"A  
144 - 162 sq. ft. / gal.

**Felt-Backed Sheet Vinyl: Sq. Notch (Porous Surfaces)**  
1/16"D x 1/16"W x 1/16"A  
140 - 160 sq. ft. / gal.

**Felt-Backed Sheet Vinyl: U-Notch (Non-Porous Surfaces)**  
1/32"D x 1/16"W x 5/64"A  
225 - 275 sq. ft. / gal.

# HENRY®

The W.W. Henry Company  
(888) 512-7339

[www.wwhenry.com](http://www.wwhenry.com)